

Peanut for WordPress Installation

1. Create your database then install WordPress or upgrade to version 4
See: https://codex.wordpress.org/Installing_WordPress
Note: Peanut has been tested using WordPress v. 4.8.1. It is designed to work on multi-site installations and sub-paths, but has only been tested for the single site environment in the document root.
2. Enable pretty URLs. On Linux/Unix systems use an .htaccess file per the example on <https://codex.wordpress.org/htaccess>
The "Basic WP" example is fine for most sites. In some WordPress installations this is already present.
3. Create test page titled 'Peanut Smoke Test'. The 'permalink' should be [http://\(your domain name goes here\)/peanut-smoke-test](http://(your domain name goes here)/peanut-smoke-test)
4. Make a database backup. It is unlikely to be needed but good to have if any installation problems occur.
5. From the distribution zip file, extract directories below 'web.root' to your WordPress root directory
6. Install the Peanut Plugin and Peanut Theme.
7. Note: The theme is dependent on the plugin and must be installed/uninstalled in order.
8. Install: First plugin then theme
9. Uninstall: First theme then plugin
10. Activate the Peanut plugin on the "Plug-ins" page:

☒ **peanut** Peanut framework supports KnockoutViewModels and TOPS Services
[Activate](#) | [Edit](#) | [Delete](#) Version 0.1 | By [Terry SoRelle](#) | [Visit plugin site](#)

11. Note when you install one of the peanut themes you will see a message like the one below under "Broken Themes" at the bottom of the "Themes" page. Click "Install Parent Theme" for the peanut theme you want to use.

| Name | Description | |
|----------------|---|---|
| peanut-philips | The parent theme is missing. Please install the "philips" parent theme. | Delete Install Parent Theme |

12. Try the Peanut Smoke Test.